

High Elasticity Cleanroom Tape

LYNBOND



ISO CLASS 6+

Low Particle Generation

Residue-Free Removal

About

High Elasticity Cleanroom Tape is engineered for use in controlled environments where cleanliness and performance are critical. Manufactured from polyethylene film with an acrylic adhesive, it provides excellent elongation, secure adhesion, and residue-free removal. Each roll is cleaned, cut, and double-bagged within an ISO Class 6 cleanroom, ensuring product integrity and suitability for high-purity applications.

Specification

- Suitable for ISO 6+ Cleanroom environments
- Polyethylene film with acrylic adhesive
- Excellent elongation and adhesion strength
- Clean removal with minimal residue
- Available in 25mm and 50mm widths (33m Length)
- Colour options: White, Blue, Green, Red, Yellow and Clear
- Dual cleanroom packing (PE bag + nylon bag)
- Suitable for marking, sealing and temporary fixing tasks

Application

- Suitable for Semiconductor manufacturing and microelectronics.
- Laboratories and Controlled Environments
- Cleanroom packaging and equipment labelling
- Surface marking and zoning within controlled areas



QUALITY MANAGEMENT SYSTEM

FACILITY HOLDING

ISO 9001:2016

Rev.27.25

High Elasticity Cleanroom Tape

LYNBOND



Property	Typical Values	Notes
Film Material	Polyethylene film	
Adhesive Type	Acrylic	-
Colours Available	White, Blue, Green, Red, Yellow, Clear	
Film Thickness	110 ± 5 µm	-
Adhesive Thickness	25 ± 5 µm	-
Adhesion to Steel	700 ± 125 g / 25mm	ASTM D3330
Operating Temperature	-6 °C to 48 °C	
Core Diameter	76 ± 2 mm (PE core)	
Roll Length	33 Metres	-
Roll Width	25mm / 50mm	-
Packaging Quantity	25mm - 60 rolls / ctn 50mm - 30 rolls / ctn	-
Cleanroom Packaging	ISO Class 6 dual PE bag system	Vacuum packed and sealed

COLOURS
White
Blue
Green
Red
Yellow
Clear

TARIFF DETAILS

COUNTRY OF ORIGIN	Republic of Korea
H/S CODE	3919100000

INVENTORY MANAGEMENT

STORAGE INSTRUCTIONS	Store in a cool, dry place (below 40°C) away from direct sunlight, fluorescent light and heat
----------------------	---

Rev.27.25